

Jib Cranes

17.1 TDAVIT Shackled



VINCA
EQUIPOS INDUSTRIALES



REID
LIFTING
Official Partner

Our **TDAVIT** is lightweight, portable, and as well as a wide range of standard sizes can be custom-designed and manufactured to specifically meet our customers' individual needs. Truly pioneering, it offers a lifting capacity of up to 600kg and 360° rotation under a full load.

Key features

- EN795:2012 Certified
- ATEX Certified
- Can support goods and personnel lifting;
 - Goods WLL of up to 600kg
 - Personnel WLL of up to 300kg
- Can be operated and assembled by one person, no tools required
- Can be rotated 360° under a full load
- Designed with a universal kingpin which is compatible for all REID sockets
- Clean, anodised finish for increased corrosion resistance
- A variety of attachments for a range of applications
- Engineered designs and bespoke sections reduce weight, providing lightweight portability

Configurations

The **TDAVIT** is available in a range of configurations and can be customised in line with specific requirements (subject to WLL rating).

**Refer to REID for further guidance



**600KG
WLL**



**1 PERSON
ASSEMBLY**



**CUSTOMISED
& BAGGED**



**EN795
CERTIFIED**



**ATEX
CERTIFIED**


Features & Performance

	BEAM 0	BEAM 1	BEAM 2	BEAM 3	BEAM 4
Accreditations, Certifications & Standards					
EN795:2012	✓	✓	✓	✓	×
AS/NZS 5532:2013	✓	✓	✓	✓	×
ATEX Certified [Zone 2]	✓	✓	✓	✓	✓
ATEX Certified [Zone 1]	Optional	Optional	Optional	Optional	Optional
IRATA	✓	✓	✓	✓	×
Capacity					
Maximum Goods Lifting [kg]	600	500	500	375	300
Maximum Personnel Lifting [kg]	300	250	250	150	×
Fall Arrest [Persons]	1	1	1	1	×
Dimensions					
Maximum Reach [mm]	650	850	1050	1450	1850
Maximum Height of Lift [mm]	2115	2290	2365	2510	2665
Socket Diameter					
65mm	✓	✓	✓	✓	✓
Socket Options					
Top Mount	✓	✓	✓	✓	✓
Flush Mount	✓	✓	✓	✓	✓
Side Mount	✓	✓	✓	✓	✓
Bridge Mount	✓	✓	✓	✓	✓
Pedestal	✓	✓	✓	✓	✓
Extension Post	✓	✓	✓	✓	✓
Standard Features					
Shackle Lifting points	✓	✓	✓	✓	✓
Component Weight < 25kg	✓	✓	✓	✓	✓
Optional Extras					
Winch Capable	✓	✓	✓	✓	✓
Rotational Handle	✓	✓	✓	✓	✓
Finishes					
Anodised	✓	✓	✓	✓	✓
316SS Fixings	Optional	Optional	Optional	Optional	Optional
Marine Spec	Optional	Optional	Optional	Optional	Optional

Dimensions in the table are approximate values. For more accurate details please refer to the Dimension Table.
 All line items marked with a '✓' come as standard. All line items marked with a 'X' are not available.
 All line items marked with 'optional' are available as an option and may incur additional costs.

TDAVIT® SHACKLED

- A** Radius | Position A
- B** Radius | Position B
- C** Height of Lift | Position A
- D** Height of Lift | Position B
- P1** Height of Pin Position 1
- P2** Height of Pin Position 2



Product Code	Description
TDSA1A0TD2	T-Davit Type S Column option 1 Beam option 0 WLL 600kg
TDSA1A1TD2	T-Davit Type S Column option 1 Beam option 1 WLL 500kg
TDSA1A2TD2	T-Davit Type S Column option 1 Beam option 2 WLL 500kg
TDSA1A3TD2	T-Davit Type S Column option 1 Beam option 3 WLL 375kg
TDSA1A4TD2	T-Davit Type S Column option 1 Beam option 4 WLL 300kg
TDSA2A0TD2	T-Davit Type S Column option 2 Beam option 0 WLL 600kg
TDSA2A1TD2	T-Davit Type S Column option 2 Beam option 1 WLL 500kg
TDSA2A2TD2	T-Davit Type S Column option 2 Beam option 2 WLL 500kg
TDSA2A3TD2	T-Davit Type S Column option 2 Beam option 3 WLL 375kg
TDSA2A4TD2	T-Davit Type S Column option 2 Beam option 4 WLL 300kg
TDSA3A0TD2	T-Davit Type S Column option 3 Beam option 0 WLL 600kg
TDSA3A1TD2	T-Davit Type S Column option 3 Beam option 1 WLL 500kg
TDSA3A2TD2	T-Davit Type S Column option 3 Beam option 2 WLL 500kg
TDSA3A3TD2	T-Davit Type S Column option 3 Beam option 3 WLL 375kg
TDSA3A4TD2	T-Davit Type S Column option 3 Beam option 4 WLL 300kg
TDSA4A0TD2	T-Davit Type S Column option 4 Beam option 0 WLL 600kg
TDSA4A1TD2	T-Davit Type S Column option 4 Beam option 1 WLL 500kg
TDSA4A2TD2	T-Davit Type S Column option 4 Beam option 2 WLL 500kg
TDSA4A3TD2	T-Davit Type S Column option 4 Beam option 3 WLL 375kg
TDSA4A4TD2	T-Davit Type S Column option 4 Beam option 4 WLL 300kg
TDSA5A0TD2	T-Davit Type S Column option 5 Beam option 0 WLL 600kg
TDSA5A1TD2	T-Davit Type S Column option 5 Beam option 1 WLL 500kg
TDSA5A2TD2	T-Davit Type S Column option 5 Beam option 2 WLL 500kg
TDSA5A3TD2	T-Davit Type S Column option 5 Beam option 3 WLL 375kg
TDSA5A4TD2	T-Davit Type S Column option 5 Beam option 4 WLL 300kg

➤ How To Specify A TDAVIT

Select a beam option from the table based on the radius you require. Each TDAVIT has two radius options A or B which is determined by the beam position [refer to the dimensional drawing on page 3].

Be aware that larger radius beams reduce the working load limit of the TDAVIT.

Select your column option from the dimensional table based on the height of lift you require. Column option 1 is our shortest standard column and option 5 is our tallest.

Should you need a greater height of lift, you can add a pedestal or socket extension, subject to restrictions [see socket overview for further information].

For our standard TDAVIT product codes refer to the product code list on page 3 for any custom requests please contact your REID representative.

To request a quote and any additional information on sockets or accessories such as winches and chain hoists, contact your local reseller or your REID representative.

TDS/DS/ENV/5/09/2021

Beam Option		0		1		2		3		4				
Dimension	A	B	A	B	A	B	A	B	A	B				
Radius [mm]*	650	590	850	775	1050	960	1450	1335	1850	1705				
WLL [kg]	600		500		500		375		300					
Weight [kg]	9		10		11		14		17					
Column Option	Dimension	C	D	C	D	C	D	C	D	C	D	Weight [kg]	P1	P2
	1	880	1100	890	1175	900	1250	920	1395	940	1550	20	980	1080
	2	1060	1280	1070	1355	1080	1430	1100	1575	1120	1730	21	1165	1265
	3	1370	1590	1380	1665	1390	1740	1410	1885	1430	2040	23	1475	1575
	4	1685	1905	1695	1980	1705	2055	1725	2200	1745	2355	25	1790	1890
	5	1995	2215	2005	2290	2015	2365	2035	2510	2055	2665	28	2100	2200

*Radii achieved at = 75% WLL

All information herein is copyright protected by REID Lifting Ltd. All company and product names are Trade Mark and Trade Name protected and all REID Product IPR is protected under Patents, Patents Pending and/or Design Rights.

Other products of the VINCA group



- **Bridge Cranes**

- Monorail, Double Girder, Light Crane or Bridge Crane Kit

- **Gantry Cranes**

- Automotive Gantry Cranes, Lightweight Gantry

- **Rotating Booms**

- Portable, Manual, Motorized, Column

- **Winches**

- Electric, manual, drill operated

- **Hoists**

- Manual, Pneumatic, Chain Electric, Cable Electric

- **Accessories for Bridge Cranes**

- Claws, Hooks, Spreader
- Dynamometers
- Turner / Tilter ü Radio Controls

- **Carts**

- **Forklifts and Vertical Lifters**

- Mixed lifts
- Automatic Lifts
- Lifts (PLT)
 - Single Frame, Double Frame

- **Scissors Lifting Tables**

- Standard, Reinforced, Electromechanical, Special
- Lifts for working at height

- **Loading Docks**

- Loading Dock Shelters
- Loading Ramps
- Mobile Ramps (RMC), Automatic, Adjustable
- Safety Equipment
 - Vehicle Immobilizers, DOK-GUARDIAN Safety Barriers, Spotlights, Trailer Stands.

- **Industrial Doors**

- Flexible Doors, Fast, Refrigerated, White Rooms, Sectionals, Firewalls.
- Gates and Locks

- **Turners, Inverters and Levelers**

- Pallet Inverter INVERTER ü NIVELMATIC Levelers
- Tilters INCLINATOR
- Tilters
- SKIPS for Transvases

- **Industrial Load Handler**

- Hook Manipulators VACU-LIFT ü Vacuum Manipulators
- Weightless Manipulators ü Mobile Lifts
- Suspension Systems

- **Industrial Fans**

- **Mobile Power Lines**

- **SAT Service**

- Maintenance, Repair



ATEX finish of the equipment on request



Official Partner

BARCELONA

Tel 93 635 61 20

Fax 93 635 61 30

info@vinca.es

MADRID

Tel: (+34) 616 91 69 82

madrid@vinca.es

VALENCIA

Tel: (+34) 647 817 537

valencia@vinca.es

GALICIA

Tel: (+34) 648 923 832

galicia@vinca.es

C/ Técnica, 39

Pol. Ind. Torre Bovera

08740 St. Andreu de la Barca

BARCELONA

www.vinca.es

